

SCHEDA USATO

SCHEDA n°	256	DATA	02.09.2013
-----------	-----	------	------------

Descrizione	VAGLIO MOBILE LOGOTRACK ST 3.5
-------------	--------------------------------

PROPRIETÀ	
-----------	--

Costruttore	METSO MINERALS
-------------	----------------

Anno di costruzione	2010	Matricola	
---------------------	------	-----------	--

Caratteristiche tecniche	TRAMOGGIA m ³ 5.5 VAGLIO mm 1500 X 3580 PIANI n. 2 NASTRO PRINCIPALE 1000 x 8.7 NASTRI LATERALI 650 x 7.7 NASTRO SABBIA 1200 x 6.1 MOTORIZZAZIONE CAT kW 75 a RPM 2.200 ORE DI FUNZIONAMENTO: < 500
--------------------------	---

Visibile Presso:	MARCHE
------------------	--------

Note caratteristiche	Macchina praticamente nuova
----------------------	-----------------------------

Prezzo	€ 125.000,00	validità	Salvo Venduto
--------	--------------	----------	---------------

Foto allegate n° 3 + spec. Metso





Lokotrack ST3.5 mobile screen

The latest edition to the Lokotrack mobile screen product range is the ST3.5. The product is designed with compact transport dimensions, high quality components, and to meet the latest global health and safety legislation.

The standard ST3.5 two-deck Lokotrack is capable of producing two sized fractions, and depending on the application, an optional two-deck vibrating grid can be installed to yield three sized fractions.

Lokotrack ST3.5 is ideal for:

from small to medium-sized contractors

efficient classification of up to three end products in wide range of screening applications

Main customer benefits of the Lokotrack ST3.5 are:

designed to achieve the lowest sustainable cost per ton
unmatched efficiency and capacity in its size class
working safety is ensured by built in safety of all components, structural solutions and low voltage control system

Main features of the Lokotrack ST3.5 are:

High capacity two bearing two deck screen box is equipped with interchangeable screen meshes minimizing customer stock holding costs. New CAT4.4 75kw (100HP) diesel engine together with efficient hydraulic system enables trouble free and cost efficient operation also in demanding applications and extreme climate conditions. Compact dimensions and low transport weight add value through lower transport costs.

Technical specifications

Screen deck area (two deck screen)	3580 mm x 1500 mm (11 ft 7 in x 5 ft)
Hopper capacity	5.5 m ³ (7.2 yd ³)
Loading height with grid	3290 mm (10 ft 9 in)
Loading width	3800 mm (12 ft 5 in)
Engine power	75 kW (100 hp)

Transport dimensions

Length:	14 350 mm (47 ft 1 in)
Width:	3000 mm (9 ft 6 in)
Height:	3460 mm (11 ft 3 in)
Weight:	23 230 kg (51,100 lbs)